F 0751

Description:

HD F 0751 is a HDPE Compound with mineral reinforcement and additives and filler. It is for Injection Moulding for applications requiring a good balance between easy of processability and flowability and mechanical properties.

Ehdapolymer:
In addition to producing quality products, our mission in Ehda polymer pack, is technical support for products as well as innovative solutions and providing appropriate formulation in the field of producing plastic products.

Applications:

it can be used for in film production

Specifications:

Property	Unit	Value	Test Method
Melt Flow Rate (MFR) (190 °C/2.16Kg)	g/10min	0.07 ± 0.02	ISO 1133
Density	g/cm3	0.937	ISO 1183
OIT	Min	≤20	---------
ASH content	%	0 ± 0.15	D5630-13

Processing Technique
Recommended Process Temperature 180-200 °c
However, the actual processing conditions depends on size, machine and formulation of the customer.

Packaging and Storage:

Packaged in 25kg PE bags. To be stored in dry and cool conditions, protected from direct sunlight and rain pour.

* Values shown are average and are not to be considered as product specification

Ehdapolymer
info@ehdapolymer.com
WhatsApp:
+90-5367299326
Address:
No.11 Mihan Alley.,
Madaen St. 11 th St, Khaje abdollah St., Shariati Rd.,
Tehran, Iran.
Tel: +98-21-26710841
Mob: +98-9058768969
www.ehdapolymer.com