HD P 2545

Description:

EHDA's **HD P 2545** is a **HDPE** compound. It contains a combination of HDPE, additives and stabilizers. Designed to obtain great processability, good thermal stability and appearance, with good mechanical properties.

Applications:

Suitable for production of various types of **Pipe**

Ehdapolymer:
In addition to producing quality products, our mission in Ehda polymer pack, is technical support for products as well as innovative solutions and providing appropriate formulation in the field of producing plastic products.

Specifications:

Property	Unit	Value	Test Method
Melt Flow Rate (MFR) 5 Kg, 190 C	g/10min	0.23±0.04	ISO 1133
Density	g/cm3	0.956	ISO 1183
Humidity	%	≤0.25	---------
OIT	min	20 ≤	----------
Carbon Balck	%	3 ± 0.2	Astm D1603

Processing Technique
Recommended Process Temperature 180-200 °c
However, the actual processing conditions depends on size, machine and formulation of the customer.

Packaging and Storage:

Packaged in 25kg PE bags. To be stored in dry and cool conditions, protected from direct sunlight and rain pour.

* Values shown are average and are not to be considered as product specification

Ehdapolymer
info@ehdapolymer.com
Address:
No.11 Mihan Alley.,
Madaen St. 11 th St, Khaje abdollah St., Shariati Rd.,
Tehran, Iran.
Tel: +98-21-26710841
Mob: +98-9058768969
www.ehdapolymer.com