EHDA PA 104

Description:

Polymer processing aids(PPA) masterbatch PA 104 is the new generation highly technical product based on fluoropolymer active content. It improves the processability of the polymers at higher shear rates. Addition of PPA Masterbatch reduces the melt fracture or shark skin effect during the process

Applications:

Film products(blown,cast), Extrusion blown moulding, Pipes and tubing (PEX,HDPE,…)

Specifications:

Property	Unit	Value	Test Method
Melt Flow Rate (MFR) (190 °C/2.16Kg)	g/10min	1 ± 0.4	ISO 1133
Density	g/cm3	0.9 ± 0.1	ISO 1183

Processing Technique
Recommended Process Temperature 180-200 °c
However, the actual processing conditions depends on size, machine and formulation of the customer.

Packaging and Storage:

Packaged in 25kg PE bags. To be stored in dry and cool conditions, protected from direct sunlight and rain pour.

* Values shown are average and are not to be considered as product specificatio

Ehdapolymer:
In addition to producing quality products, our mission in Ehda polymer pack, is technical support for products as well as innovative solutions and providing appropriate formulation in the field of producing plastic products.

Ehdapolymer
info@ehdapolymer.com
Address:
No.11 Mihan Alley.,
Madaen St. 11 th St, Khaje abdollah St., Shariati Rd.,
Tehran, Iran.
Tel: +98-21-26710841
Mob: +98-9058768969
www.ehdapolymer.com